

EGO3AA Video Tripod System

Great camera balance can be achieved due to the counterbalance feature with the built-in spring. The fluid torque system contributes to smooth operation. The EG03AA is an ideal entry-level tripod system for home video shootings and for digital single-lens reflex camera users. Its max.load is 5kg (11lbs). Max.height is 160.5cm, min.height is 77.5cm, transport length is 81.5cm. Mid-level Spreader and kit bag is included.



Specifications:

Payload	5.0kg / 11.0lbs
Height range	77.5-160.5cm / 30.5-63.2in
Transport length	81.5cm / 32.1in
Net weight	4.9kg / 10.8lbs
Bowl size	75mm

What's included:

Head	GH03	
Tripod	AT7402A	
Packing	SC-1 Carry bag	

GHO3 75mm Fluid Head

The E-Image GH03 fluid head with 75mm ball supports cameras and accessories weighing up to 5kg (11lbs). The GH03 head features an easy lock baseplate system that combines the balance adjustment of a sliding baseplate with the ease of a quick release system. It provides a fixed counterbalance settings that helps the fluid head support loads up to 5kg (11lbs) and won't force you to fight the head when working with lightweight camera systems.



Features



Continuous adjustable of tilt drag.



GP1 quick release plate.



A built-in bubble level to assist balancing.




Additional 1/4"-20 screw hole for articulating accessories.


Specifications

MAX	Payload	5.0kg / 11.0lbs
(A)	Counterbalance	Fixed
الن	Grades of pan drag	Fixed
4	Grades of tilt drag	Continuous adjustable

Ó	Tilt range	-80°~+90°
	Temperature range	-40°C~+80°C
Q	Net weight	1.3kg / 2.9lbs
_	Bowl size	75mm

Counterbalance Graph







AT7402A 75mm Video Tripod

The AT7402A 2-stage aluminum tripod legs with 75mm bowl base, support payload up to 40kg (88lbs) and provide 66-149cm (26-58.7in) working height range. Designed with a fixed mid-level spreader, dual foot spikes with removable anti-slip pads and rotary leg locks for flexible and stable operations. It also includes an integrated leg wrap bungee and clip for your safe and convenient carrying.



Specifications:

Payload	40.0kg / 88.0lbs
Height range	66.0-149.0cm / 26.0-58.7in
Transport length	70.0cm / 27.6in
Net weight	3.6kg / 7.9lbs
Bowl size	75mm
Sections	3
Material	Aluminum

Recommend accessories

