

Presidential Series Teleprompter

E-IMAGE presidential series teleprompter delivers professional prompting with a robust aluminum structure, supporting 15"/17"/19"/24" monitors via a 15cm adjustable slot for easy compatibility. Plus an optional 19" LED monitor with necessary cables and hardwar for out-of-the-box setup, saving debugging time.It features a 36×30cm anti-reflection coated beamsplitter (50:50 ratio,3mm tempered glass), ensuring clear prompting and transparent audience view. With smooth height adjustment, 45°–75° tilt range, built-in sunshield, and 5.2m reading range, it is ideal for conferences, presentations, and professional video applications.

TPS-01



Specifications

Model	TPS-01
Height Range	55.5-174cm / 21.9-68.5in
Section	5
Max.Tube Dia.	36mm
Base Feet Type	Adjustable
Net Weight	3.3kg/7.3lbs
Stand Material	Aluminum

Beamsplitter Glass

Beam Splitter Ratio	50:50
Beamsplitter Glass Size	360x300mm (Optional: 400x400mm)

TPS-02



Model	TPS-02
Height Range	84-188cm / 33.1-74.0in
Section	4
Max.Tube Dia.	36mm
Base Feet Type	360° Wheels with brakes
Net Weight	4.6kg/10.1lbs
Stand Material	Aluminum

Support	15"/17"/19"/24" Monitors
Beamsplitter Glass Rotation	45°-75°

Features

- Aluminum alloy structure, stable and durable.
  - Fast, easy setup with necessary cables and hardware.
  - Fit for different size monitors with adjustable 15cm slot.
  - Sunshield hood is included.
- Beamsplitter size : 360x300mm (14.2x11.8").
  - Beamsplitter tilt angle range : 45°-75°.
  - Anti-reflection coating prevent glass reflections.
  - Reading range up to 5.2m (17").

Recommend kit

TPS-01K



TPS-02K



19" Monitor Features

- Dimension : 19" LED monitor.
- Interface : 12V DC+ HDMI IN+ HDMI OUT+ VGA+AUDIO+USB.
- Brightness : 350CD/M2.
- Resolution : 1280x1024.
- LED Backlight.
- VESA standard mount.
- Size : 423x348x52mm.

